

SBARCO

Model T4ES-300M

Entry level printer – Easy to operate

- Ultra Modern 3D indicator light design
- Simple to operate
- Large memory, large storage space
- The most affordable price
- Moveable transmission sensor
- Modified print head for efficient label printing



Model T4ES-300M	
Resolution	203/300 dpi
Print mode	Direct Thermal/Thermal Transfer
CPU	32-bit CPU
Memory	<ul style="list-style-type: none"> RAM: 64 MB SDRAM ROM: 128 MB Flash ROM
Print speed	203 dpi 1 to 5 ips (option up to 6 ips) / 300 dpi 4 ips
Max. print length	150" (3810 mm)
Print width	4,1" (104 mm)
Sensor type	<ul style="list-style-type: none"> Moveable reflective sensor Ribbon sensor Moveable transmission sensor Cover open sensor
Display	N/A
Control panel	<ul style="list-style-type: none"> 1 multi-functional keys 6 status LED light
Media	<ul style="list-style-type: none"> Maximum label width: 4,33" (110 mm) Minimum label width: 0,59" (15 mm) Maximum roll diameter: 5" (127 mm) core diameter: 1,0" (25,4 mm) upto 1,5" (38 mm) with adapter Media thickness: 0,002" (0,06 mm) to 0,0075" (0,2 mm) Media type: Continuous, die-cut, tag, fan-fold, black mark
Ribbon	<ul style="list-style-type: none"> OD: 1,535" (39 mm) Max length: 100 m Width: 1,0" (25,4 mm) to 4,3" (110 mm) ID: 0,5" (12,7 mm) Ribbon type: Wax, wax/resin, resin
Interfaces	<ul style="list-style-type: none"> USB slave port Ethernet port 10/100 Mbps
1D barcodes	Code39 standard or extended, Code39 with check digit, Code93, Code 128 UCC, Code128 auto A modes, Codabar, EAN8, EAN8/13 2&5 digit add-on, EAN 13, Interleaved 2 of 5, Interleaved 2 of 5 check digit, Interleaved 2 of 5 with human readable check digit, UCC/EAN 128, UPC A, UPC A 28 add-on, UPC E, UPC E 2&5 digit add-on, UPC Interleaved 2 of 5, Code11
2D barcodes	Data Matrix, MaxiCode, PDF417, QR code
Fonts	<ul style="list-style-type: none"> 5 internal expandable bitmap fonts (alpha-numeric) 2 internal expandable bitmap fonts (numeric only) Downloadable soft font 4 directions: 0, 90, 180, 270 degrees
Image	<ul style="list-style-type: none"> PEPL: PCX, Direct binary graphic PDPL: PCX, BMP, HEX
Options	<ul style="list-style-type: none"> Peeler kit Cutter BT moule, WiFi module
Power	<ul style="list-style-type: none"> Switching power adapter Input: 100 to 240V, 1,8A, 50 ~ 60 Hz Output: 24V, 2,5A
Audio	N/A
Real Time Clock	N/A
Environment	<ul style="list-style-type: none"> Operation: 5 °C to 45 °C (40 °F to 112,9 °F) Storage: -20 °C to 50 °C (-4 °F to 121,9 °F)
Humidity	<ul style="list-style-type: none"> Operation: 10 % to 90 % non condensing Storage: 5 % to 95 % non condensing
Printer dimension	<ul style="list-style-type: none"> Width: 200,00 mm (7,83") Lenght: 263, 19 mm (10,36") Hight: 188,29 mm (7,41") Weight: 2 kg
Certification	CE, FCC class A, CB, CCC, BSMI

Specifications subject to change without notice. Copy right 2010 Sbarco Technology All right reserved.
SBARCO is a registered trade mark of Sbarco technology Co., Ltd.

SBARCO

THE ONE YOU CAN RELY ON